

An Approximate Search Engine for Structural Databases*

Jason T. L. Wang[†] Xiong Wang[‡] Dennis Shasha[§] Bruce A. Shapiro[¶]

Kaizhong Zhang^{||} Qicheng Ma^{**} Zasha Weinberg^{††}

1 Background

When a person interested in a topic enters a keyword into a Web search engine, the response is nearly instantaneous (and sometimes overwhelming). The impressive speed is due to clever inverted index structures, caching, and a domain-independent knowledge of strings. Our project seeks to construct algorithms, data structures, and software that approach the speed of keyword-based search engines for queries on structural databases.

A structural database is one whose data objects include trees, graphs, or a set of interrelated labeled points in two, three, or higher dimensional space. Examples include databases holding (i) protein secondary and tertiary structure, (ii) phylogenetic trees, (iii) neuroanatomical networks, (iv) parse trees, (v) molecular diagrams, and (vi) XML documents. Comparison queries on such databases require solving variants of the graph isomorphism or subisomorphism problems (for which all known algorithms are exponential), so we have

* Work supported by NSF grants IRI-9531548, IRI-9531554, and by the Natural Sciences and Engineering Research Council of Canada under Grant No. OGP0046373.

[†] Dept. of Computer & Information Science, New Jersey Institute of Technology, University Heights, Newark, NJ 07102 (jason@cis.njit.edu).

[‡] Dept. of CIS, NJIT, NJ 07102 (xiong@cis.njit.edu).

[§] Courant Institute of Mathematical Sciences, New York University, New York, NY 10012 (shasha@cs.nyu.edu).

[¶] Experimental and Computational Biology Lab, National Cancer Institute, Frederick, MD 21702 (bshapiro@ncifcrf.gov).

^{||} Dept. of Computer Science, University of Western Ontario, London, Ontario, N6A 5B7, Canada (kzhang@csd.uwo.ca).

^{**} Dept. of CIS, NJIT, NJ 07102 (qicheng@cis.njit.edu).

^{††} Dept. of Computer Science & Engineering, University of Washington, Seattle, WA 98195 (zasha@cs.washington.edu).

Permission to make digital or hard copies of part or all of this work or personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers, or to redistribute to lists, requires prior specific permission and/or a fee.

MOD 2000, Dallas, TX USA

© ACM 2000 1-58113-218-2/00/05 . . . \$5.00

explored a large heuristic space.

2 Prototype

We have two different search techniques: one based on topological relationships and the other based on physical position. In SIGMOD 2000 we will demo a search engine capable of answering the following queries on a structural database \mathcal{D} containing 3D graphs:

- (1) [nearest-neighbor query] Given a query object o , which items o' in \mathcal{D} are “closest” to o ? We have experimented with two different similarity scores. The score between a graph g_1 and a graph g_2 based on an alignment M is defined as the fraction of edges in g_1 (g_2 , respectively) that are consistent in g_2 (g_1 , respectively) based on M . Edge $\{i, j\}$ of g has a consistent edge in g' based on the alignment M if $\{M[i], M[j]\}$ is an edge in g' . The larger the score between g_1 and g_2 , the closer g_1 is to g_2 . We use this query to illustrate our search technique based on topological relationships.
- (2) [discovery query] Which substructures approximately occur in all items in \mathcal{D} ? A substructure may occur in a graph after allowing for an arbitrary number of whole-structure rotations and translations as well as a small number (specified by the user) of edit operations in the substructure or in the graph. (When a substructure appears in a graph only after the graph has been modified, we call that appearance “approximate occurrence.”) The edit operations include relabeling a node, deleting a node and inserting a node. We use this query to illustrate our discovery technique based on physical position. We can search by physical position and discover by topological relationships.

For both queries, we will show the best alignment information in addition to graphically displaying the qualifying (sub)structures.